

MULLION VANDAL RESISTANT READER 125 KHZ - 2 WIRES

FD-020-118



The vandal resistant surface mount reader is a 125KHZ proximity reader used with IPassan and Ipervoice solutions. Elegant and durable, it is ideal for indoor and outdoor installations. This reader is perfect for offices, commercial properties and residential housing.

Functioning:

Led of the reader is red when it is ready to read a proximity key. When a key is presented to the reader, the red led flashes when the key is refused and if the key is valid the led turns green during the programmed door release time.

Technical characteristics



125 kHz

- Dimensions (W x H x D): 100mmx45mmx16mm
- Power supply: 12V DC (supplied by the controller)
- Current: 30mA
- Wire gauge: 2 wires / 100m max
- Reading distance: up to 15mm
- Buzzer
- Operating Temperature: -10 ° to + 50 ° C
-

Disclaimer: Whilst every effort has been made to ensure accuracy in the representation of this product, neither FDI MATELEC nor its employees, shall be liable under any circumstances to any party in respect of decisions or actions they may make as a result of using this information. In accordance with the FDI MATELEC policy of enhanced development, design and specifications are subject to change without notice.



Produits associés obligatoires

Accessoires

FD-010-070
LOT DE 10 CARTES
ISO 125 KHZ

Disclaimer: Whilst every effort has been made to ensure accuracy in the representation of this product, neither FDI MATELEC nor its employees, shall be liable under any circumstances to any party in respect of decisions or actions they may make as a result of using this information. In accordance with the FDI MATELEC policy of enhanced development, design and specifications are subject to change without notice.

