



Easy Door Receiver is an RF access control system for small residential applications. It is an all-in-one product (controller and receiver) which has been designed for 2 gates and can manage up to 2000 users.

The same product can be managed either away from its installation place (remote management or so called Virtual Network Mode) or on site (standalone mode).

For remote management, all you need is an internet connection for our web software www.easydoorcontroller.com and our USB encoder. Then you have to:

1-Note the controller N° of the installed product (written on top label)

2-Register on www.easydoorcontroller.com

3-Program the transmitters/keys using the encoder which records one or several n° of allowed doors inside the transmitter.

To remotely delete permissions for a transmitter, you simply have to cancel that transmitter on the website and program a new one instead. At the first use of the new one on the controller, the old transmitter will be blocked instantly.

Technical characteristics

			
13.56 MHz 868 MHz	1 to 2 doors	1 to 2000 users	Programming via web software

- Dimensions (W x H x D): 120mmx100mmx40mm
- Programming on site with master key or with programming terminal
- Wiring: 2 max fils/100m between the controller and reader
- Power supply: 12/24 Vac or Vdc
- Control relay: NC / NO
- Adjustable timer from 1 to 99 seconds
- Removable connections
- Operating temperature: -20 ° C to +60 ° C

Mandatory related products

Accessories



Complementary related products

Accessories



Disclaimer: Whilst every effort has been made to ensure accuracy in the representation of this product, neither FDI MATELEC nor its employees, shall be liable under any circumstances to any party in respect of decisions or actions they may make as a result of using this information. In accordance with the FDI MATELEC policy of enhanced development, design and specifications are subject to change without notice.

